


CRA 耐硫化厚膜チップ抵抗器 Anti-Sulfurated Thick Film Chip Resistors

寸法・形状 Dimensions



表示：抵抗面に捺印
E24：3数字表示
CRA10：無表示
Marking：Print on the resistive surface.
E24series：3-digits
CRA10：No marking

形名 Type	寸法 Dimensions : mm				
	L	W	a	b	t
CRA10	1.0±0.05	0.5±0.05	0.2±0.1	0.25+0.05-0.1	0.35±0.05
CRA16	1.6±0.1	0.8±0.1	0.3±0.2	0.3±0.2	0.45±0.1
CRA21	2.0±0.1	1.25±0.1	0.4±0.2	0.4±0.2	0.5±0.1
CRA32	3.2±0.2	1.6±0.15	0.5±0.2	0.5±0.2	0.6±0.1
CRAB32	3.2±0.2	2.5±0.15	0.5±0.2	0.5±0.2	0.6±0.1
CRA50	5.0±0.2	2.5±0.15	0.6±0.2	0.5±0.2	0.6±0.1
CRA63	6.3±0.2	3.2±0.2	0.7±0.2	0.7±0.2	0.6±0.1

定格 Rating

形名 Type	定格 Power rating	最高使用電圧 Max. working voltage	最高過負荷電圧 Max. overload voltage	抵抗値許容差 Resistance tolerance	抵抗値範囲 Resistance range	使用温度範囲 Operating temperature range
CRA10	0.063W	50V	100V	J G F	10Ω~1MΩ	-55℃ ~ +125℃
CRA16	0.1W	50V	100V			
CRA21	0.125W	150V	300V			
CRA32	0.25W	200V	400V			
CRAB32	0.33W	200V	400V			
CRA50	0.75W	200V	400V			
CRA63	1W	200V	400V			

形名構成 How to code

CRA
形名
Type

16
寸法・定格
Dim./rating

10	0.063W
16	0.1W
21	0.125W
32	0.25W
B32	0.33W
50	0.75W
63	1W

TR
包装仕様
Packaging

TR	REEL
----	------

公称抵抗値
Nominal res.


E24

J
抵抗値許容差
Res. tolerance

J	±5%
G	±2%
F	±1%

CRF ファンクショントリマブル厚膜チップ抵抗器 Trimmable Thick Film Chip Resistors

寸法・形状 Dimensions



表示：無し
Marking：no marking

形名 Type	寸法 Dimensions : mm				
	L	W	a	b	t
CRF10	1.0±0.05	0.5±0.05	0.2±0.1	0.25+0.05-0.1	0.35±0.05
CRF16	1.6±0.1	0.8±0.1	0.3±0.2	0.3±0.2	0.45±0.1
CRF21	2.0±0.1	1.25±0.1	0.4±0.2	0.4±0.2	0.5±0.1
CRF32	3.2±0.2	1.6±0.15	0.5±0.2	0.5±0.2	0.6±0.1
CRFB32	3.2±0.2	2.5±0.15	0.5±0.2	0.5±0.2	0.6±0.1
CRF50	5.0±0.2	2.5±0.15	0.6±0.2	0.5±0.2	0.6±0.1
CRF63	6.3±0.2	3.2±0.2	0.7±0.2	0.7±0.2	0.6±0.1

定格 Rating

形名 Type	定格 Power rating	最高使用電圧 Max. working voltage	最高過負荷電圧 Max. overload voltage	抵抗値許容差 Resistance tolerance	抵抗値範囲 Resistance range	使用温度範囲 Operating temperature range
CRF10	0.063W	50V	100V	K M S W R L	1Ω~1MΩ	-55℃ ~ 125℃
CRF16	0.063W	50V	100V			
CRF21	0.1W	100V	200V			
CRF32	0.125W	200V	400V			
CRFB32	0.25W	200V	400V			
CRF50	0.5W	200V	400V			
CRF63	1W	200V	400V			

形名構成 How to code

CRF
形名
Type

16
寸法・定格
Dim./rating

10	0.063W
16	0.063W
21	0.1W
32	0.125W
B32	0.25W
50	0.5W
63	1W

TR
包装仕様
Packaging

TR	REEL
----	------

公称抵抗値
Nominal res.

E24

K
抵抗値許容差
Res. tolerance

K	±10%
M	±20%
S	0~-5%
W	0~-10%
R	0~-20%
L	0~-30%